

BRIGHTBAY FOCUSQUARE

FINNS I DIMBART UTFÖRANDE

ART.NR	STORLEK	STYRKA	INSPÄNNING	LED ANTAL	FÄRG TEMP.	FLÖDE LM	CRI	MATERIAL	SPRID-VINKEL	IP KLAS
BW-T36-100W	400*125*230mm	100W	AC100~277V 50~60Hz	28st CREE/ SEOUL3535	3000K-3500K 4000K-4500K 5500K-6500K	8000- 9000lm	>70	Aluminium & PC	60° 30°X70°	IP65
BW-T36-100W+	400*125*230mm	100W	AC100~277V 50~60Hz	112st SM3030	3000K-3500K 4000K-4500K 5500K-6500K	10000- 11500lm	>80	Aluminium & PC	120°	IP65
BW-T36-150W	295*260*230mm	150W	AC100~277V 50~60Hz	56st CREE/ SEOUL3535	3000K-3500K 4000K-4500K 5500K-6500K	14500- 15500lm	>70	Aluminium & PC	60° 30°X70°	IP65
BW-T36-150W+	295*260*230mm	150W	AC100~277V 50~60Hz	224st SM3030	3000K-3500K 4000K-4500K 5500K-6500K	13500- 15500lm	>80	Aluminium & PC	120°	IP65
BW-T36-230W	295*395*230mm	230W	AC100~277V 50~60Hz	84st CREE/ SEOUL3535	3000K-3500K 4000K-4500K 5500K-6500K	16500- 18500lm	>70	Aluminium & PC	60° 30°X70°	IP65
BW-T36-230W+	295*395*230mm	230W	AC100~277V 50~60Hz	336st SM3030	3000K-3500K 4000K-4500K 5500K-6500K	20500- 24000lm	>80	Aluminium & PC	120°	IP65
BW-T36-300W	590*260*230mm	300W	AC100~277V 50~60Hz	112st CREE/ SEOUL3535	3000K-3500K 4000K-4500K 5500K-6500K	27000- 31500lm	>70	Aluminium & PC	60° 30°X70°	IP65
BW-T36-300W+	590*260*230mm	300W	AC100~277V 50~60Hz	448st SM3030	3000K-3500K 4000K-4500K 5500K-6500K	33000- 37500lm	>80	Aluminium & PC	120°	IP65
BW-T36-450W	590*395*230mm	450W	AC100~277V 50~60Hz	168st CREE/ SEOUL3535	3000K-3500K 4000K-4500K 5500K-6500K	40500- 47000lm	>70	Aluminium & PC	60° 30°X70°	IP65
BW-T36-450W+	590*395*230mm	450W	AC100~277V 50~60Hz	672st SM3030	3000K-3500K 4000K-4500K 5500K-6500K	50000- 56000lm	>80	Aluminium & PC	120°	IP65